

EXCELLENT OPACITY

GOOD ELASTICITY

FOR CONCRETE AND ASPHALT



MATCH POINT

Series 0294

Water-based paint for sports fields, cycle and pedestrian paths made of cementitious material



◆ General information

Nature: Water-based

Packages: 18 kg

Tinting Service: Can be colored with Acquaplast 0400 Series water-based colorants

Color cards: Ral 841 GL

◆ Technical features

Paint based on modified acrylic binders and high quality, outdoor resistant, selected extenders. The product is easy to apply and has excellent opacity and good elasticity. It can be applied directly on new and compact substrates, without the application of primer or fixative paint.

◆ Application field

The product is particularly suitable for painting outdoors concrete sports fields such as tennis courts, five-a-side football, basketball, volleyball, as well as bleachers, recreational spaces and cycle and pedestrian paths in concrete and asphalt.

◆ Technical data

Theoretical average spreading rate 5,2 m²/kg each coat at the dry film thickness of 60 μ

Application Roller, Brush, Spray

Dilution 5-15% with water for application on concrete; ready to be used for application on asphalt

Gloss -

Wet film thickness each coat 162 μ

Dry film thickness each coat 60 μ

N° of coats 1 or 2 coats till reaching the total, suitable thickness

Total dry film thickness 80 μ

◆ Drying

Overcoating interval 4 - 5 hours

Air drying 20°C - 25°C

Dust-free drying -

Dry to touch 1 - 2 hours

Dry through 24 hours

Full cure 4 days

Flash off -

Stoving drying -