

WATER-BASED CLEAR COATS

EXCELLENT AESTHETIC FINISH

SURFACE HARDENESS

ODOURLESS

AQUAFLOOR

Series 8210

2K, water-based acrylic clearcoat for cementitious floors



General information

System: Two pack - 2K

Nature: Water-based

Packages: 3,3 kg



Technical features

Water-based, acryl-polyurethane clearcoat based on acrylic resins and non-yellowing cross linking agents. The product has a good aesthetic appearance and surface hardness and is also suitable for outdoor application thanks to the aliphatic polymers.

Application field

Product ideal as clear, acrylic topcoat to be applied both as anti-dust, thin film thickness coat on new, rough or uncoated cementitious floors, and as transparent protective coat on previously applied, colored coats to guarantee greater durability and resistance outdoors and indoors.

Technical data

Theoretical average spreading rate 6,7 m²/kg each coat at the dry film thickness of 60 µ

Application Short Hair Roller, Brush

Dilution 10-15 % with tap water

Gloss 65 - 70 gloss

Wet film thickness each coat 139 µ

Dry film thickness each coat 60 µ

N° of coats 1

Total dry film thickness 60 µ

Drying

Overcoating interval 8 - 24 hours

Air drying 20°C

Dust-free drying 40 - 60 minutes

Dry to touch 2 - 3 hours

Dry through 36 - 48 hours

Full cure 7 days

Flash off -

Stoving drying -

Catalysis

Series	Hardener	Catalysis	Use	Pot Life at 20°C	Package
1610	PUR HARDENER FOR WB PAINTS	30% by weight (100 + 30)	Non-yellowing for water-based polyacrylic products	2 hours	1 kg