

SOLVENT-BASED CLEAR COATS

FAST DRYING

EXCELLENT OPACITY

PROTECTIVE EFFECT

ACRIFLOOR

Series 8240

2K, solvent-based acrylic clearcoat for cementitious floors



◆ General information

System: Two pack - 2K

Nature: Solvent-based

Packages: 3 l



◆ Technical features

Solvent-based clearcoat based on acrylic resins and non-yellowing cross linking agents. The product has a good aesthetic appearance and surface hardness and is also suitable for outdoor application thanks to the aliphatic polymers.

◆ Application field

Product ideal as clear, acrylic topcoat to be applied both as anti-dust, thin film thickness coat on new, rough or uncoated cementitious floors, and as transparent protective coat on previously applied, colored coats to guarantee greater durability and resistance outdoors and indoors.

◆ Technical data

Theoretical average spreading rate *8,7 m²/l each coat at the dry film thickness of 60 µ*

Application *Brush, Short Hair Roller*

Dilution *Ready to be used; max 5% with Thinner for Polyurethanes and Acrylics Series D0003*

Gloss *75 - 85 gloss*

Wet film thickness each coat *115 µ*

Dry film thickness each coat *60 µ*

N° of coats *1*

Total dry film thickness *60 µ*

◆ Drying

Overcoating interval *8 - 96 hours*

Air drying *20°C*

Dust-free drying *20 - 30 minutes*

Dry to touch *2 - 3 hours*

Dry through *24 - 36 hours*

Full cure *14 days*

Flash off *-*

Stoving drying *-*

◆ Catalysis

Series	Hardener	Catalysis	Use	Pot Life at 20°C	Package
1392	HS PLUS 420 HARDENER	30% by weight (100 + 30)	For high solid,slow for outdoor	3 hours	1 l